

Indoor Siren

Art. no. SG1250

Page 1 of 1



- LED to display armed/disarmed status
- Simple, inconspicuous design
- Selectable volume
- Low power consumption
- Impact-resistant housing monitored for tampering
- Sound pressure: 90 dB (A) – low, 110 dB (A) – high
- Protection class: IP54

The inside siren is installed inside your building. It is the last and critical module of a complete alarm chain. The inside siren is an acoustic signal generator. You have a choice between two alarm modes in this case: A 110 dB alarm and a 90 dB acknowledgement tone. Both signals are felt to be extremely loud due to the high acoustic pressure and the signal frequency. The remotely activated LED of the alarm siren can be used to detect the status of the alarm panel (armed/disarmed). The rugged plastic housing (IP 54) of the acoustic signal generator is protected against sabotage by a wall and cover contact. The inside siren is powered with 12 V.

Technical Data:

Dimensions	(WxHxD) 155x100x48 mm
Width	155 mm
Housing material	ABS
Height	100 mm
Length	48 mm
Power consumption	3,6
Illuminant	LED
Max. battery life	50 year(s)

Min. operating temperature	-10 °C
Installation location	Indoors
Tamper monitoring	Yes
Sound pressure	90/110 dB
IP protection class	54
DC voltage supply	12 V
Power consumption	300 mA