

TVAC19000B

WLAN pan/tilt camera & app

Effective all-around monitoring indoors This WLAN pan/tilt camera comes with the compatible app for iOS or Android and offers brilliant image quality at any time of day or night with a resolution of 720p. The camera can monitor 350° in the panning range and 90° in the tilting range. Thanks to the app, installation is quick and easy even for technical laymen. Event notification and mobile access via app Movement within the field of vision of the camera triggers recording on the SD card. If desired, you will be informed of incidents by e-mail or push notification and can take a snapshot or access the corresponding video image data using the app. Using the app, you also have access to the image material of up to eight cameras at the same time, enabling mobile monitoring wherever you are. The effective data compression of the camera relieves the network and increases storage space.



Product highlights:

- For effective all-around monitoring of interior spaces
 - Guided step-by-step installation via app (iOS, Android)
 - App access of up to 8 cameras
 - HD 720p resolution and infrared night vision function for brilliant image quality
 - E-mail notification, snapshot function and push notification via app when motion is detected
 - All-around visibility (350° panning and 90° tilting range)
 - Recording to SD card (accessory, max. 32 GB)
 - Low network load thanks to compressed data transfer (H.264 compression)
-

TVAC19000B

WLAN pan/tilt camera & app

Technical Data

Number of IR LEDs	5	Net weight	0,35	kg
Resolution	HD 1280 x 720 incl. audio	Range of night vision function	3	m
Recording resolution @ frame rate per camera	720p @ 5/ 10/ 20 fps (max) images per second	DC voltage supply	5	V
Image sensor	MP CMOS	Power consumption	1500	mA
Horizontal angle	50°±3°	Video compression	H.264	
Width	80 mm	Network access	Ethernet (10/100 Base-T/Base-TX); Wi-Fi (IEEE 802.11 b/g/n)	
Focal length	2,8 mm	IR LEDs	5 IR Power LEDs	
Frequency	2,4 GHz	Number of users	3 simultaneous access sessions	
Height	115 mm	Frame rate	VGA @ 20 fps / VGA @ 25fps / 720p @ 5 fps / 720p @ 10 fps	
IR cut filter	Yes	Encryption	WPA /WPA2/WPA2-PSK (TKIP, 128 bit AES)	
Length	87 mm			
Max. operating temperature	50			
Min. operating temperature	-10			