

Tube Camera Module with 3.7 mm Pinhole Lens

Art. no. IPCS10003

Page 1 of 2



- HD 720p resolution: 1280 x 720
- 3.7 mm needle eye lens
- Angle of view: 57°
- 8 m cable length
- Ideal for discreet video surveillance
- Includes a compatible bracket

The tube-shaped camera module is a required accessory for the Dual Flex Encoder IPCS10020. The mini module measures just 40 x 26 mm and has an 8 m cable for connection to the encoder, which runs from the back of the device. With an angle of view of 57°, the 3.7 mm pinhole lens gives a focused view of selected areas of a room or into corridors.

Camera eye behind a wall or ceiling or inside a machine

The tiny module, which is not much bigger than a cigarette lighter, is ideal for installation behind a wall or suspended ceiling, in gaps and passageways, in a horizontal shaft or pipe (with cabling routed backwards), or in a cash machine or other type of machine. An adhesive fixture for drill-free mounting flush with a wall (flush-mounting) or behind the metal panelling of a machine is included in the scope of delivery.

A variety of applications

The camera module is not much bigger than a cigarette lighter or a ballpoint pen. It is ideal for inconspicuous, near-invisible surveillance of indoor spaces in financial institutions/banks, shops, hotels or lifts.

Disclaimer:

The legal situation with regard to hidden surveillance may vary considerably from country to country or from region to region. Please check the applicable provisions in your installation location before installing the product.

Tube Camera Module with 3.7 mm Pinhole Lens

Art. no. IPCS10003

Page 2 of 2

Technical Data:

Dimensions	26x40 mm
Image sensor	1/3" Progressive Scan CMOS Sensor
Pixels (effective)	1280 x 960 pixel
Pixels (total)	1280 x 960 pixel
Width	26 mm
Focal length	3,7 mm
Gross weight	0,5 kg
Height	40 mm
Horizontal angle of view	57 °
Compatible with	IPCS10020

Max. resolution @ frame rate	1280 x 720 @ 25 fps
Max. operating temperature	50 °C
Min. operating temperature	-10 °C
Minimum illumination (color)	1
Minimum illumination (B/W)	1
Net weight	0,29 kg
IP protection class	24
Certifications	CE, RoHS, REACH