

Eycasa Family Care Camera

Art. no. CASA30400

Page 1 of 2

-
- Wireless colour camera for indoors
 - Wireless range up to 30 m from the main unit, depending on the situation in the building
 - Secure, digital wireless transmission
 - With night view function (IR LEDs)
 - For use as a baby monitor or for senior care
 - Automatic activation on noise detection (camera, main unit)
 - Intercom and integrated lullaby function
 - Flexible installation on gooseneck mount
-

More than just a camera

With its attractive white design, the Eycasa Family Care camera offers more than just video monitoring. Designed for indoor use, the colour camera communicates securely via wireless. The transmission range to the main unit is up to 30 metres, depending on the conditions in the building.

Baby monitor and senior care

The Family Care camera has an unobtrusive white design and is equipped with infrared night-view LEDs to identify persons at close range, as well as a noise detection function. If a noise is detected, the camera and the main unit are automatically activated. This means the Family Care camera can be used as a baby monitor or for people in need of care.

Useful functions for families

The camera can also be decorated with the jolly stickers supplied in the package, so that looks just right in the baby's bedroom. In addition, the camera has a lullaby function. This enables it to play up to five different lullabies.

Eycasa Family Care Camera

Art. no. CASA30400

Page 2 of 2

Technical Data:

Video frequency	2,4 Ghz
Video modulation	FHSS+GFSK
Video data rate	800 kbps
Video transmission power	13,5 dBm
Video sensitivity	-82 dBm
Audio frequency	1,9 Ghz
Audio modulation	TMDA
Audio transmission power	< 20 dBm
Audio sensitivity	-82 dBm
Audio data rate	64 kbps
Dimensions	69 x 117 x 32 mm
Alarming	VOX trigger to Eycasa Main unit
Connectible devices	Eycasa main unit
Number of IR LEDs	7 IR LEDs
Resolution	640 x 480 Pixel (VGA)
Battery type	Lithium Polymer Akku 1200 mAh / 3.7 V
Operating mode	Permanent power connection of battery mode
Image sensor	1/4" CMOS
Frame rate	20 fps
Width	315 mm

Focal length	3,27 mm
Wireless range	30 (depending on the site conditions) m
Height	135 mm
Horizontal angle of view	54 °
IR angle	90 °
IR range	ca. 3 m
IR cut filter	No
Length	32 mm
Loudspeaker	8 Ohm / 1 x 1Watt
Max. operating temperature	-10 - 50 °C
Microphone	Integrated
IP protection class	34
DC voltage supply	5 V
Power consumption	max. 850 mA
Video compression	MPEG-4