

Secvest Wireless Magnetic Contact CC (white)

Art.-Nr. FUMK50000W



- Reliably detects opening of windows, doors, etc.
- Connection option for further wired detectors
- Can be used as wireless module
- Tamper surveillance

Reliable alarm triggering in the event of intrusionThe wireless opening detector detects and reports the unauthorised opening of doors and windows using a magnetic contact. In such cases, it informs the wireless alarm panel, which then triggers a corresponding alarm. Detection and reportingThis product consists of a detector and a magnet. These components are mounted parallel to each other on the moving part of the window or door and on the window or door frame. The detector triggers as soon as the distance between the two contact points is increased when the window or door is opened. The components can be mounted on the bottom window frame in order to allow a window to be tilted open without disrupting the magnetic contact. Even greater protection with additional wired alarm zonesThe wireless opening detector also allows the wiring of additional detectors in order to effectively enhance intrusion protection. The detector can be connected to a passive glass breakage detector, for example, which can be mounted to the window pane and detects window breakages. The wireless opening detector for the Secvest wireless alarm system is available in white and brown.

Secvest Wireless Magnetic Contact CC (white)

Art.-Nr. FUMK50000W

Technical Data

Battery type	3 V CR2 Li/MnO2
Certifications	INCERT, VSÖ, F&P, NCP
Connections	Screw terminal (CC)
DC voltage supply	3V
Environmental class	I
Height	89mm
Housing material	ABS
Installation location	Windows, doors
Length	29mm
Max. battery life	2year(s)
Max. operating temperature	55°C
Max. sending range (building)	30m
Max. sending range (outdoors)	100m
Min. operating temperature	-10°C
Modulation	FM

Net weight	0.05kg
Power consumption	30mA
Power consumption	0,09
Radio frequency	868,6625MHz
Security level	2
Sensor type	Reed contact
Status display	Yes
Tamper monitoring	Yes
Transmission power	10
Type of detection	Magnetic field measurement
Voltage monitoring	Yes
Width	33mm