

Vector HD 900 + 2x0,75mm



Composite cable for CCTV systems
 HD-SDI / HD- CVI / HD-TVI / A-HD
 1 x Vector HD 900 + 2 x 0,75 mm²
 CPR Certified

A. COAXIAL

A1. CONSTRUCTION

Inner Conductor	Φ0,80mm Bare copper
Insulation	Φ 3,50mm skin-foam-skin gas injected PE
Outer Conductor	Al-Pet-Al tape + Al wire braid
Outer Sheath	Φ 5,00mm PVC white

A2. ELECTRICAL CHARACTERISTICS

Impedance	75 +/-3 Ohm
Capacitance	53 pF/m
Velocity ratio (v/c)	0,85
Sheath Spark Test	3 KV
Nom. Attenuation (dB/100m)	
10 MHz	2,90
100 MHz	9,80
1500 MHz	32,00

Vector HD 900 + 2x0,75mm

B. FEEDING CORES

Nr of cores X cross section	2 x 0,75 mm ²
Conductor construction	24 x Φ 0,20mm Bare copper
Cores Insulation	Φ 2,00, PVC a. black b. red

C. OUTER SHEATH

Outer Sheath	6,3mm x 8,6mm PVC White
Min. bending radius for one bend	45 mm
for repeated bending	90 mm

D. OTHER DATA

Standards	
CPR Class	Eca
DOP	1002549
Connectors	BNC(m)-3950
Συσκευασία	4x100 m 1x400 m